

X-17



▶ FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 3ms response time
- High 800 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security socket
- VESA standard wall mount
- Available colors: black, white



▶ SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	17.0" (432mm)	
	Max. Resolution	SXGA 1280 x 1024	
	Pixel Pitch	0.264mm	
	Brightness	300cd/m ² (Typical)	
	Contrast Ratio	800:1 (Typical)	
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment	
	Viewing Angle (H/V)	160°/160° (Typical)	
	Display Color	16.7M	
	Response Time	3ms (GTG)	
Input	Frequency (H/V)	H: 30kHz - 80kHz V: 56Hz - 75Hz	
	Max. Pixel Clock	135MHz	
Connector	Life Time	50,000hrs (Minimum)	
	Analog	15-Pin D-Sub	
	Digital	24-Pin DVI-D	
	S-Video*	4-Pin Mini Din S-Video	
NeoV Optical Glass	CVBS*	CVBS Jack	
	Power	3-Pin AC Plug	
	Thickness	3.0mm (0.18")	
	Reflection Rate	<1%	
Tilt	Transmission Rate	>96%	
	Hardness	>6H (MOH's Rating)	
	Tilt	0° ~ +15°	
Mounting	VESA FPMPI	Yes (100mm)	
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/Baurt, CE, BSMI, CB, ISO 13406-2, EPA, GOST, WEEE, RoHS	
	VESA	DDC 2B, DPMS	
Power	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off)	
	Dimensions	Net (W x H x D)	408 x 398 x 175mm (16.1" x 15.7" x 6.9")
		Packing (W x H x D)	495 x 510 x 228mm (19.5" x 20.0" x 9.0")
Weight	Net Weight	6.8Kg (13.9lbs)	
	Gross Weight	9.5Kg (20.9lbs)	
Packing	1 Pallet	40 Cartons	
	20' Container	360 Sets	
	40' Container	840 Sets	

*Video inputs are optional functions

All specifications are subject to change without prior notice



www.agneovo.com

Copyright © 2007 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of Associated Industries China, Inc.
All other trademarks are the property of their respective owners.